








































# Bulldog® recycling rotating nozzles

## Bulldog® rotating nozzle 1/2" - 3/4"

						
	<b>400.037</b>	<b>401.037</b>	<b>406.037</b>	<b>400.037C</b>	<b>401.037C</b>	<b>406.037C</b>
	1/2	1/2	1/2	3/4	3/4	3/4
	2 - 8	2 - 8	2 - 8	2 - 8	2 - 8	2 - 8
	10.5	10.5	16	10.5	10.5	10.5
	6 × M6	6 × M6	6 × M6	6 × M6	6 × M6	6 × M6
	—	—	—	—	—	—
	1 × M6	—	2 × M6	1 × M6	—	2 × M6
	1.5 × 3.3	1.5 × 3.8	1.5 × 3.8	1.5 × 3.5	1.5 × 3.9	1.5 × 3.9
	0.89	0.89	0.89	0.93	0.93	0.93
	2,900	2,900	2,900	2,900	2,900	2,900
	✓	✓	✓	✓	✓	✓

			
	<b>400.037S</b>	<b>401.037S</b>	<b>406.037S</b>
	1/2	1/2	1/2
	2 - 8	2 - 8	2 - 8
	10.5	10.5	10.5
	6 × M6	6 × M6	6 × M6
	3 × M4	3 × M4	3 × M4
	1 × M6	—	2 × M6
	1.5 × 3.3	1.5 × 3.8	1.5 × 3.8
	0.91	0.91	0.91
	2,900	2,900	2,900
	✓	✓	✓

	Connecting thread [inch]		Rotating nozzles		Maximum pressure [psi]
	Application range [inch]		Thrust jet		Recycling
	min. gpm at 1450 psi at the nozzle		Front jet	*	Option
	Measures [inch]		Weight [lb.]		

# Bulldog® recycling rotating nozzles



## Skid for Bulldog 37

<b>00100.03720</b>		1/2
		3 - 8
		2.4 x 4.3
		0.56



## Skid for Bulldog 37

<b>00100.03720C</b>		3/4
		3 - 8
		2.4 x 4.3
		0.56




	Connecting thread [inch]		Rotating nozzles		Maximum pressure [psi]
	Application range [inch]		Thrust jet		Recycling
	min. gpm at 1450 psi at the nozzle		Front jet	*	Option
	Measures [inch]		Weight [lb.]		

# Bulldog® recycling rotating nozzles

## Bulldog® rotating nozzle 3/4" - 1"



	400.060A	400.060B	400.060BS
	3/4	1	1
	4 - 12	4 - 12	4 - 12
	26	26	26
	6 × M8	6 × M8	6 × M8
	6 × M8	6 × M8	6 × M8
	1 × M8	1 × M8	1 × M8
	2.4 × 6	2.4 × 6	2.4 × 6
	4.6	4.6	4.6
	2,900	2,900	2,900
	✓	✓	✓



	402.080LS100	404.080HS100	402.080LS150	404.080HS150	400.080SET100 / 400.080SET150
	1	1	1	1	1
	6 - 16	6 - 16	8 - 16	8 - 16	8 - 16
	53	53	53	53	53
	6 × M10	6 × M10	6 × M10	6 × M10	6 × M10
	(6 × M8)*	(6 × M8)*	(6 × M8)*	(6 × M8)*	(6 × M8)*
	1 × M10	1 × M10	1 × M10	1 × M10	1 × M10
	3.9 × 8.7	3.9 × 8.7	5.9 × 10.2	5.9 × 10.2	5.9 × 10.2
	8.22	8.22	12.82	12.82	12.82
	2,900	2,900	2,900	2,900	2,900
	✓	✓	✓	✓	✓

LS = slow turning

HS = fast turning

\* Thrust can be closed with the thrust stop piece

	Connecting thread [inch]		Rotating nozzles		Maximum pressure [psi]
	Application range [inch]		Thrust jet		Recycling
	min. gpm at 1450 psi		Front jet	*	Option
	Measures [inch]		Weight [lb.]		

High Performance Tool

enz golden jet®

# Bulldog® recycling rotating nozzles




## Skid for Bulldog 60

<b>00100.0807</b>		1
		6 - 16
		ØxL 3.9 x 8.7
		2.43



## Skid for Bulldog 80

<b>00100.0808</b>		1
		8 - 16
		ØxL 5.9 x 10.2
		6.32



## Thrust stop

<b>00100.08073</b>		
<b>OR18.0200</b>	O-Ring	

High Performance Tool **enz golden jet®**

	Connecting thread [inch]		Rotating nozzles		Maximum pressure [psi]
	Application range [inch]		Thrust jet		Recycling
	min. gpm at 1450 psi		Front jet	*	Option
	Measures [inch]		Weight [lb.]		

# Bulldog® recycling rotating nozzles

## Bulldog® rotating nozzle 1"



**400.101A**

	1
	8 - 24
	53
	3 × M10 2 × M10 90°
	6 × M10
	1 × M10
	5 × 10
	16.0
	2,900
	✓



**401.101A**

	1
	8 - 24
	53
	6 × M10 90°
	—
	1 × M10
	5 × 10
	16.0
	2,900
	✓



**401.101AS**

	1
	8 - 24
	53
	6 × M10 90°
	6 × M10
	1 × M10
	5 × 10
	16.0
	2,900
	✓



**400.101B**

	1 1/4
	8 - 24
	53
	3 × M10 2 × M10 90°
	6 × M10
	1 × M10
	5 × 10
	16.0
	2,900
	✓



**401.101B**

	1 1/4
	8 - 24
	53
	6 × M10 90°
	—
	1 × M10
	5 × 10
	16.0
	2,900
	✓




**401.101BS**

	1 1/4
	8 - 24
	53
	6 × M10 90°
	6 × M10
	1 × M10
	5 × 10
	16.0
	2,900
	✓

	Connecting thread [inch]		Rotating nozzles		Maximum pressure [psi]
	Application range [inch]		Thrust jet		Recycling
	min. gpm at 1450 psi		Front jet	*	Option
	Measures [inch]		Weight [lb.]		


# Bulldog® recycling rotating nozzles

## Skid for Bulldog 100



<b>100.1019A</b>		1 1/4 - 1
		10 - 31
		8 x 11
		11

## Skid for Bulldog 100



<b>100.1019B</b>		1 1/4 - 1 1/4
		10 - 31
		8 x 11
		10.7

## Cage universal (without nozzle)



<b>100.1004RA</b>	with rolls		1 1/4 - 1
			15 - 39.3
			15 x 22.8
			21.1

<b>100.1004RAW</b>	without rolls		1 1/4 - 1
			15 - 39.3
			15 x 22.8
			21.1

## Cage universal (without nozzle)



<b>100.1004RB</b>	with rolls		1 1/4 - 1 1/4
			15 - 39.3
			15 x 22.8
			21.1

<b>100.1004RBW</b>	without rolls		1 1/4 - 1 1/4
			15 - 39.3
			15 x 22.8
			21.1

	Connecting thread [inch]		Rotating nozzles		Maximum pressure [psi]
	Application range [inch]		Thrust jet		Recycling
	min. gpm at 1450 psi		Front jet	*	Option
	Measures [inch]		Weight [lb.]		