


Flounder

Flounder 1/2" - 1 1/4"



70.050

| | |
|--|--------------------------|
| | 1/2 |
| | 6 - 10 |
| | 16 |
| | S1: 2 × M8 S2: 2 × M8 |
| | S1: 15° S2: 7.5° |
| | 7.7 × 3.5 × 1.4 |
| | 5.78 |
| | 3,625 |
| | ✓ |




70.075

| | |
|--|--------------------------|
| | 3/4 |
| | 8 - 16 |
| | 26 |
| | S1: 2 × M8 S2: 4 × M8 |
| | S1: 10° S2: 0° |
| | 7.7 × 3.9 × 2.0 |
| | 7.11 |
| | 3,625 |
| | ✓ |



70.100

| | |
|--|---|
| | 1 |
| | 12 - 24 |
| | 53 |
| | S1: 2 × M10 S2: 2 × M10 S3: 4 × M10 |
| | S1: 15° S2: 7.5° S3: 0° |
| | 13.4 × 6.3 × 2.2 |
| | 27.35 |
| | 3,625 |
| | ✓ |



70.125

| | |
|--|---|
| | 1 1/4 |
| | 16 - 31 |
| | 66 |
| | S1: 2 × M10 S2: 4 × M10 S3: 4 × M10 |
| | S1: 15° S2: 7.5° S3: 0° |
| | 15.0 × 7.1 × 2.8 |
| | 42.22 |
| | 3,625 |
| | ✓ |

| | | | | | |
|--|------------------------------------|--|--------------------|--|------------------------|
| | Connecting thread [inch] | | Thrust jet | | Weight [lb.] |
| | Application range [inch] | | Front jet | | Recycling |
| | min. gpm at 1450 psi at the nozzle | | Jet angle backward | | Maximum pressure [psi] |
| | Length × Width × Height [inch] | | Measures [inch] | | |

High Performance Tool **enz** golden jet®